



### INA PME30-N bearing units

Bearing No. PME30-N

Bore Diameter	30 mm
d	30 mm
U	24,7 mm
Thread (Q)	M6
Z	80 mm
d3	44 mm
A	20,5 mm
A1	9,5 mm
B1	35,8 mm
H	125 mm
J	100 mm
N	11,5 mm
S	2 mm
A2	2 mm
Weight	0,97 Kg
Basic dynamic load rating (C)	19,5 kN
Category	Flange Block Bearings
Inventory	2.0
Manufacturer Name	SCHAEFFLER GROUP
Minimum Buy Quantity	N/A
Weight / Kilogram	1.162
EAN	4012802812718
Product Group	M06110
Number of Mounting Holes	4
Mounting Method	Eccentric Collar
Housing Style	4 Bolt Round Flange

PME30-N Bearing 2D drawings and 3D CAD models



## Lamar parts manufacturing company

	Cartridge
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	11.5 Millimeter
Relubricatable	Yes
Insert Part Number	GRAE30NPPB
Seals	Double Lip Contact
Housing Configuration	1 Piece Solid
Pilot Configuration	With Pilot
Inch - Metric	Metric
Long Description	4 Bolt Round Flange Cartridge; 30MM Bore; 99MM Bolt Circle; 70.7MM Bolt Spacing; 1 Piece Solid; Eccentric Collar Mount; Cast Iron; Ball Bearing; 35.7MM Length Thru Bore; Relubricatable; Double Lip Con
Other Features	Single Row   Centering Spigot   With Set Screw
Category	Flange Block
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Flanged
Manufacturer URL	<a href="http://www.ina.com">http://www.ina.com</a>
Manufacturer Item Number	PME30N
Weight / LBS	2.139
Length Thru Bore	1.406 Inch   35.7 Millimeter
Cartridge Pilot Diameter	3.15 Inch   80 Millimeter
Bore	1.181 Inch   30 Millimeter
Nominal Bolt Circle Diameter Round	3.9 Inch   99 Millimeter



## Lamar parts manufacturing company

Bolt Spacing	2.783 Inch   70.7 Millimeter
Cartridge Pilot Depth	0.354 Inch   9 Millimeter